



## Residential SimpleSteam™ Generator Sizing

Follow the steps below to select the proper SimpleSteam™ Steam Generator for your steam shower.

**STEP 1: MEASURE THEN MULTIPLY** the Length x Width x Height (in feet) of the steam enclosure to determine cubic footage.

**STEP 2: ADJUST CUBIC FOOTAGE** to determine Adjusted Room Volume.

**Material Adjustments:**

- For ceramic or porcelain tile, glass or glass block, multiply by 1.35.
- For natural stone or marble, multiply by 2.0.
- If using another material, consult Delta Steam Customer Service for their recommendation.

**Exterior Wall Adjustments:** For one, multiply by 1.1; for two, multiply by 1.2, etc.

**Ceiling Height Adjustments:** For 9 ft. ceiling, multiply by 1.15; for 10 ft. ceiling, multiply by 1.3.

- For optimum performance, **ceiling height** should not exceed 8 feet (10 feet max).

**STEP 3: SELECT STEAM GENERATOR** within the Adjusted Room Volume range shown below.

- If there is a **skylight or outside window**, select the next largest generator. The skylight or window must be double-pane and sealed from inside the steam shower.
- **Generator voltage** must match existing local utilities (240 Volts).

Model Number	kW	Adjusted Room Volume Range	Electrical			Dimensions (LxWxH)	Weight
			Volts	Amps	Double Pole Breaker*		
5P-EST04-XX	4	00-65	240	17	20	15" x 6" x 15 ½"	30 lbs
5P-EST06-XX	6	66-150	240	25	30	15" x 6" x 15 ½"	30 lbs
5P-EST07-XX	7.5	151-250	240	31	40	15" x 6" x 15 ½"	30 lbs
5P-EST10-XX	10	251-450	240	42	50	15" x 6" x 15 ½"	30 lbs
5P-EST12-XX	12	451-550	240	50	60	17 ¾" x 7 ½" x 15 ½"	41 lbs
5P-EST15-XX	15	551-675	240	63	80	17 ¾" x 7 ½" x 15 ½"	41 lbs

- Finish suffix must be added to replace the "-XX"
- \*90°C copper wire required for connection to generator.



Our Steam Configurator makes it simple to personalize your at-home steam experience. Choose your generator, steam head, controls and more.

**For more information or questions, please contact Delta Steam Customer Service: 800-394-6478.**



## Residential SteamScape™ Generator Sizing

Follow the steps below to select the proper SteamScape™ Steam Generator for your steam shower.

**STEP 1: MEASURE THEN MULTIPLY** the Length x Width x Height (in feet) of the steam enclosure to determine cubic footage.

**STEP 2: ADJUST CUBIC FOOTAGE** to determine Adjusted Room Volume.

**Material Adjustments:**

- For ceramic or porcelain tile, glass or glass block, multiply by 1.35.
- For natural stone or marble, multiply by 2.0.
- If using another material, consult Delta Steam Customer Service for their recommendation.

**Exterior Wall Adjustments:** For one, multiply by 1.1; for two, multiply by 1.2, etc.

**Ceiling Height Adjustments:** For 9 ft. ceiling, multiply by 1.15; for 10 ft. ceiling, multiply by 1.3.

- For optimum performance, **ceiling height** should not exceed 8 feet (10 feet max).

**STEP 3: SELECT STEAM GENERATOR** within the Adjusted Room Volume range shown below.

- If there is a **skylight or outside window**, select the next largest generator. The skylight or window must be double-pane and sealed from inside the steam shower.
- **Generator voltage** must match existing local utilities (208, 220, or 240 Volts).

Model Number	kW	Adjusted Room Volume Range	Electrical			Dimensions (LxWxH)	Weight
			Volts	Amps	Double Pole Breaker*		
5GE-SMP05-240-1	5	00-100	240	21	30	15" x 6" x 15 ½"	30 lbs
5GE-SMP07-240-1	7.5	101-250	240	31	40	15" x 6" x 15 ½"	30 lbs
5GE-SMP10-240-1	10	251-450	240	42	50	15" x 6" x 15 ½"	30 lbs
5GE-SMP12-240-1	12	451-550	240	50	60	17 ¾" x 7 ½" x 15 ½"	41 lbs
5GE-SMP15-240-1	15	551-675	240	63	80	17 ¾" x 7 ½" x 15 ½"	41 lbs

- For 208 Volt, 1-phase generators replace "-240" with "-208" to Product Code. Example: 5GE-SMP10-208-1
- For 208 Volt, amperage will be higher and breaker size larger. Contact Delta Customer Service for more information.
- For 220 Volt, please contact Delta Customer Service for special order options.
- For 3-phase generators, please contact Delta Customer Service for special order options.
- \*90°C copper wire required for connection to generator.



Our Steam Configurator makes it simple to personalize your at-home steam experience. Choose your generator, steam head, controls and more.

**For more information or questions, please contact Delta Steam Customer Service: 800-394-6478.**



**COMMERCIAL**

## Delta® Commercial Generator Sizing

Follow the steps below to select the proper Delta® Commercial Steam Generator for your steam room.

**STEP 1: MEASURE THEN MULTIPLY** the Length x Width x Height (in feet) of the steam enclosure to determine cubic footage.

- **Generator voltage** must match existing local utilities (208, 240, or 480 Volts).
- For optimum performance, **ceiling height** should not exceed 8 feet (10 feet max).

kW	Adjusted Room Volume Range	Model Number	Electrical				Dimensions (LxWxH)	Weight
			Volts	Phase	Amps	Breaker Size*		
9	0-400	5COM09-PAC-609-240-01	240	1	38	50	21" x 19" x 25"	200 lbs
		5COM09-PAC-609-208-01	208	1	43	60		
		5COM09-PAC-609-240-03	240	3	22	30		
		5COM09-PAC-609-208-03	208	3	25	35		
12	401-500	5COM12-PAC-612-240-01	240	1	50	70	21" x 19" x 25"	200 lbs
		5COM12-PAC-612-208-01	208	1	58	80		
		5COM12-PAC-612-208-03	208	3	33	45		
		5COM12-PAC-612-480-03	480	3	15	20		
15	501-620	5COM15-PAC-615-240-01	240	1	63	80	21" x 19" x 25"	200 lbs
		5COM15-PAC-615-208-01	208	1	72	90		
		5COM15-PAC-615-208-03	208	3	42	60		
		5COM15-PAC-615-480-03	480	3	18	25		
18	621-740	5COM18-PAC-618-240-01	240	1	75	100	21" x 19" x 25"	200 lbs
		5COM18-PAC-618-240-03	240	3	43	60		
		5COM18-PAC-618-208-03	208	3	50	70		
		5COM18-PAC-618-480-03	480	3	22	30		
24	741-1000	5COM24-PAC-624-240-01	240	1	100	125	21" x 19" x 25"	200 lbs
		5COM24-PAC-624-208-01	208	1	115	150		
		5COM24-PAC-624-240-03	240	3	58	80		
		5COM24-PAC-624-208-03	208	3	67	90		
		5COM24-PAC-624-480-03	480	3	29	40		
30	1001-1250	5COM30-PAC-630-240-03	240	3	72	90	39" x 22" x 28"	300 lbs
		5COM30-PAC-630-208-03	208	3	84	110		
		5COM30-PAC-630-480-03	480	3	36	45		
36	1251-1500	5COM36-PAC-636-240-03	240	3	87	110	39" x 22" x 28"	300 lbs
		5COM36-PAC-636-208-03	208	3	100	125		
		5COM36-PAC-636-480-03	480	3	44	60		
48	1501-2000	5COM48-PAC-648-240-03	240	3	116	150	39" x 22" x 28"	300 lbs
		5COM48-PAC-648-208-03	208	3	133	175		
		5COM48-PAC-648-480-03	480	3	58	80		

- \*90°C copper wire required for connection to generator.

**For more information or questions, please contact Delta Steam Customer Service: 800-394-6478.**